



STRIKE FIRST
FIRE EXTINGUISHERS



REGULAR
BC DRY CHEMICAL



Meets or exceeds:
ANSI/UL 299 & 711

English / Spanish labels



Meets or exceeds:
CAN/ULC-S504 & S508

English / French labels

Built tough and easy to service

STRIKE FIRST Regular
BC fire extinguishers
are designed for:



CLASS B
flammable liquids & gases



CLASS C
electrical conductivity

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Reinforced, full grip steel handles with polyester powder paint finish
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service

Complies with NFPA 10 Standard

Meets D.O.T. Requirements

U.S.C.G. approved with bracket listed on label

Temperature range: -65°F to 120°F (-54°C to 49°C)

6 Year Warranty



CAPACITY	2.75 lb	5 lb	10 lb	20 lb
UL Model No.	SF-SB275	SF-SB5	SF-SB10	SF-SB20
ULC Model No.	WBDL-SB275	WBDL-SB5	WBDL-SB10	WBDL-SB20
UL Rating	10-B:C	10-B:C	60-B:C	80-B:C
ULC Rating	10-B:C	10-B:C	60-B:C	80-B:C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)
Discharge Time	9 sec	13 sec	15 sec	28 sec
PSI	150	195	235	235
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	21 1/4" (54 cm)	24" (61 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)
Weight	4 3/4 lb (2.2 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)
Chrome Option	YES	-	YES	-
Standard Bracket	Vehicle / Marine	Wall or Vehicle/Marine	Wall	Wall
Optional Brackets	Wall UP2-DB	UB-5DB UB-5MD HDVB-1	UP-10MD HDVB-2	HDVB-3



STRIKE FIRST
CORPORATION

777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767
TF 1 888 575-1132
F 416 299-8039
TF 1 888 575-1134

E info@strike-first.com
www.strike-first.com