





Meets or exceeds: ANSI/UL 8 & 711

English / Spanish labels



Meets or exceeds: CAN/ULC-S554 & S508

English / French labels



Built tough and easy to service

STRIKE FIRST Wet Chemical fire extinguishers are designed for:



CLASS A wood, paper, cloth



CLASS K restaurant, kitchen hazard

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Factory filled and pressurized

Complies with NFPA 10 Standard

Meets D.O.T. Requirements

Temperature range: 35°F to 120°F (2°C to 49°C)

5 Year Warranty



| CAPACITY | 1.6 gallons (6 litres) |
|------------------|------------------------|
| UL Model No. | SF-6LK |
| ULC Model No. | WBDL-6LK |
| UL Rating | 1-A : K |
| ULC Rating | 1-A : K |
| Range | 8 - 10 ft (2.4 - 3 m) |
| Discharge Time | 55 sec |
| PSI | 100 |
| Height | 21 1/2" (54.6 cm) |
| Width | 8 3/4" (22 cm) |
| Diameter | 7 1/8" (18 cm) |
| Weight | 24 1/2 lb (11.1 kg) |
| Standard Bracket | Wall |

The STRIKE FIRST Class K extinguisher is designed for use on restaurant or commercial cooking appliances. The low Ph wet chemical agent effectively smothers and cools fires involving combustible cooking oil (vegetable) or animal fat.

It is intended to be used as a back-up for an automatic fire suppression system.

