

# CARBON DIOXIDE



**STRIKE FIRST**  
FIRE EXTINGUISHERS



**6 YEAR  
WARRANTY**

**WHEN  
SECONDS  
COUNT.**



## **Built Tough and Ready to Serve**

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin and retaining chain
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. approved cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)

**STRIKE FIRST Carbon Dioxide  
Fire Extinguishers are designed for:**



**B**

**FLAMMABLE  
LIQUIDS  
& GASES**



**C**

**ELECTRICAL  
EQUIPMENT**



**LISTED**

**MEETS OR EXCEEDS:**  
ANSI/UL 154 & 711



**LISTED  
HOMOLOGUÉ**

**MEETS OR EXCEEDS:**  
CAN/ULC-S503 & S508



Manufacturing  
Fire Equipment  
**for over 35 Years**



CAPACITY	5 lbs	10 lbs	15 lbs	20 lbs
Model No.	SF-5CO2	SF-10CO2	SF-15CO2	SF-20CO2
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size II	Type B:C Size II	-
Range	6-12 ft (1.8-3.7 m)	6-12 ft (1.8-3.7 m)	6-12 ft (1.8-3.7 m)	6-12 ft (1.8-3.7 m)
Discharge Time	11 sec	12 sec	17 sec	22 sec
Height	17 1/4" (44 cm)	19 3/4" (50.2 cm)	26 1/4" (66.7 cm)	26 1/4" (66.7 cm)
Width	8 1/2" (21.6 cm)	11 3/4" (30 cm)	11 3/4" (30 cm)	12" (30.5 cm)
Diameter	5 1/4" (13.3 cm)	7" (17.8 cm)	7" (17.8 cm)	8" (21 cm)
Weight	13 1/2 lb (6.12 kg)	28 lb (12.7 kg)	37 lb (16.78 kg)	48 1/8 lb (21.8 kg)
Standard Bracket	Wall / VB	Wall / VB	Wall / VB	Wall
Optional Brackets	HDVB-2	HDVB-3	HDVB-3	-



777 Tapscott Road  
Scarborough  
Ontario, Canada M1X 1A2

P 416 299-7767  
TF 1 888 575-1132

F 416 299-8039  
TF 1 888 575-1134

[info@strike-first.com](mailto:info@strike-first.com) | [www.strike-first.com](http://www.strike-first.com)