

WATER MIST



STRIKE FIRST
FIRE EXTINGUISHERS



5 YEAR
WARRANTY

**WHEN
SECONDS
COUNT.**



Built Tough and Ready to Serve

- Stainless steel cylinder powder coat white
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- QR and Bar-coded labels for accurate service
- Shipped empty without pressure
- MR Conditional Approval: 7-Tesla or less
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

**STRIKE FIRST Water Mist
Fire Extinguishers are designed for:**



A

WOOD
PAPER
& CLOTH



C

ELECTRICAL
EQUIPMENT



LISTED

MEETS OR EXCEEDS:
ANSI/UL 8 & 711



LISTED
HOMOLOGUÉ

MEETS OR EXCEEDS:
CAN/ULC-S554 & S508



Manufacturing Fire Equipment for over 35 Years

**A**

WOOD
PAPER
& CLOTH

**C**

ELECTRICAL
EQUIPMENT

The STRIKE FIRST Water Mist Extinguisher is an ideal solution for Class A and Class C fire hazards.

Utilizing Type I ultra-pure deionized water (sold separately SF-WM250R), it discharges an ultra-fine water mist that effectively suppresses fires while minimizing water damage. Safe for use on energized electrical equipment, it is particularly well suited for hospitals, data and communication rooms, museums, archives, schools, and other sensitive environments.

The extinguisher leaves no chemical residue, making cleanup simple and helping protect valuable equipment and assets. Additionally, the STRIKE FIRST Water Mist Extinguisher is MR Conditional approved for use in magnetic resonance imaging environments up to 7-Tesla.



CAPACITY	2.4 GALLONS (9L)
Model No.	SF-WM250
UL/ULC Rating	2-A : C
Range	10 ft (3.1 m)
Discharge Time	120 secs
PSI	100
Height	25" (63.5 cm)
Width	9" (22.9 cm)
Diameter	7" (17.8 cm)
Weight	8.5 lbs (3.9kg)
Standard Bracket	Wall



MR CONDITIONAL

The 9L Water Mist Fire Extinguisher is MR Conditional. Testing have demonstrated that this product can be used in an MRI environment according to the following conditions: Static magnetic field of 7-Tesla or less.

IMPORTANT NOTE: This product is intended for use inside the MRI environment (e.g., in the MR system room, close to the scanner). However, it should not be utilized directly inside the MR system (e.g., inside the bore of the scanner) while the test is operating.



STRIKE FIRST
FIRE EXTINGUISHERS

777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767 TF 1 888 575-1132

info@strike-first.com | www.strike-first.com